

// 286EE



**Water discharge - PVC - Lay flat - Standard duty**

**Tube:** blue PVC.  
**Reinforcement:** high tensile textile cords.  
**Cover:** blue PVC - abrasion and ozone resistant.  
**Application:** lay flat water discharge.  
**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"			5	75	15	225				0,210	0,15
51,0	2"			5	75	15	225				0,270	0,19
63,0	2 1/2"			4	60	12	180				0,380	0,26
76,0	3"			4	60	12	180				0,530	0,36
102,0	4"			4	60	12	180				0,710	0,48
152,0	6"			3	45	9	135				1,180	0,80
203,0	8"			3	45	9	135				1,800	1,21

// 288HH



**Water discharge - PVC - Lay flat - Heavy duty**

**Tube:** red PVC.  
**Reinforcement:** high tensile textile cords.  
**Cover:** red PVC - abrasion and ozone resistant.  
**Application:** lay flat water discharge.  
**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"			10	150	30	450				0,250	0,17
32,0	1 1/4"			10	150	30	450				0,300	0,21
38,0	1 1/2"			10	150	30	450				0,330	0,23
45,0	1 3/4"			10	150	30	450				0,430	0,29
51,0	2"			8	120	24	350				0,480	0,33
63,0	2 1/2"			8	120	24	350				0,590	0,40
76,0	3"			7	100	21	300				0,770	0,52
102,0	4"			6	90	18	270				0,980	0,66
152,0	6"			5	75	15	225				1,600	1,08