

Dimensions shown may be changed without prior notice

// 250AA

**Water discharge 5 bar (75 psi) - Lay flat****Tube:** black EPDM.**Reinforcement:** high tensile textile cords.**Cover:** black EPDM - abrasion and ozone resistant.**Application:** lay flat water discharge.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		↷		%		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in			kg/m	lb/ft
102,0	4"	110,00	4,33	5	75	15	225					1,670	1,13
152,0	6"	160,00	6,30	5	75	10	150					2,430	1,64
203,0	8"	213,00	8,39	5	75	10	150					3,260	2,20
254,0	10"	264,00	10,39	5	75	10	150					4,010	2,70

// 253AA

**Water discharge 10 bar (150 psi) - Lay flat****Tube:** black EPDM.**Reinforcement:** high tensile textile cords.**Cover:** black EPDM - abrasion and ozone resistant.**Application:** lay flat water discharge.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		↷		%		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in			kg/m	lb/ft
32,0	1 1/4"	40,00	1,57	10	150	30	450					0,460	0,31
38,0	1 1/2"	46,00	1,81	10	150	30	450					0,540	0,37
40,0	1 9/16"	48,00	1,89	10	150	30	450					0,570	0,39
45,0	1 3/4"	53,00	2,09	10	150	30	450					0,660	0,45
51,0	2"	59,00	2,32	10	150	30	450					0,730	0,50
60,0	2 3/8"	68,00	2,68	10	150	30	450					0,860	0,58
63,0	2 1/2"	71,00	2,80	10	150	30	450					0,900	0,61
70,0	2 3/4"	80,00	3,15	10	150	30	450					1,380	0,93
76,0	3"	86,00	3,39	10	150	30	450					1,480	1,00
90,0	3 1/2"	100,00	3,94	10	150	30	450					1,720	1,16
102,0	4"	112,00	4,41	10	150	30	450					2,040	1,38
127,0	5"	139,00	5,47	10	150	30	450					2,730	1,84
152,0	6"	164,00	6,46	10	150	30	450					3,360	2,26
168,0	6 5/8"	180,00	7,09	10	150	30	450					3,560	2,40
203,0	8"	217,00	8,54	10	150	20	300					4,810	3,24
254,0	10"	270,00	10,63	10	150	20	300					7,680	5,17
305,0	12"	319,00	12,56	10	150	20	300					8,870	5,97