

// 375AA



Hot water-car heater 10 bar (150 psi)

Tube: black EPDM.

Reinforcement: high tensile textile cords.

Cover: black EPDM - heat, abrasion and ozone resistant.

Application: general purpose-hot water.

Specially designed for automotive heating systems.

Constant operation: -35 °C +100 °C (-31 °F +212 °F)

↔		↔		↻		↻		⤴		⚠	♻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	19,00	0,75	10	150	30	450	130,0	5,12		0,235	0,16
16,0	5/8"	22,00	0,87	10	150	30	450	160,0	6,30		0,280	0,19
19,0	3/4"	27,00	1,06	10	150	30	450	190,0	7,48		0,445	0,30
25,0	1"	33,00	1,30	10	150	30	450	250,0	9,84		0,570	0,39

60

INDUSTRIAL HOSE

// 352AA



Radiator 5 bar (75 psi)

exceeds DIN 73411 - SAE 20R1 D-2

Tube: black EPDM - DIN 73411/A compliant.

Reinforcement: high tensile textile cords.

Cover: black EPDM - heat, abrasion and ozone resistant - DIN 73411/A compliant.

Application: radiator.

Constant operation: -40 °C +120 °C (-40 °F +248 °F)

↔		↔		↻		↻		⤴		⚠	♻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	21,00	0,83	5	75	15	225				0,280	0,19
16,0	5/8"	24,00	0,94	5	75	15	225				0,330	0,23
18,0	23/32"	26,00	1,02	5	75	15	225				0,380	0,26
20,0	13/16"	28,00	1,10	5	75	15	225				0,390	0,27
22,0	7/8"	30,00	1,18	5	75	15	225				0,420	0,29
25,0	1"	33,00	1,30	5	75	15	225				0,470	0,32
28,0	1 1/8"	36,00	1,42	5	75	15	225				0,510	0,35
30,0	1 3/16"	38,00	1,50	5	75	15	225				0,550	0,37
32,0	1 1/4"	40,00	1,57	5	75	15	225				0,580	0,39
35,0	1 3/8"	43,00	1,69	5	75	15	225				0,620	0,42
38,0	1 1/2"	48,00	1,89	5	75	15	225				0,860	0,58
40,0	1 9/16"	50,00	1,97	5	75	15	225				0,890	0,60
42,0	1 5/8"	52,00	2,05	5	75	15	225				0,930	0,63
45,0	1 3/4"	55,00	2,17	5	75	15	225				0,990	0,67
48,0	1 7/8"	58,00	2,28	5	75	15	225				1,050	0,71
51,0	2"	61,00	2,40	5	75	15	225				1,120	0,76
55,0	2 1/6"	65,00	2,56	5	75	15	225				1,190	0,80
57,0	2 1/4"	67,00	2,64	5	75	15	225				1,230	0,83
60,0	2 3/8"	70,00	2,76	5	75	15	225				1,290	0,87
63,0	2 1/2"	73,00	2,87	5	75	15	225				1,350	0,91
70,0	2 3/4"	80,00	3,15	5	75	15	225				1,450	0,98
76,0	3"	86,00	3,39	5	75	15	225				1,560	1,05
80,0	3 1/8"	90,00	3,54	5	75	15	225				1,640	1,11
90,0	3 1/2"	102,00	4,02	5	75	15	225				2,030	1,37
102,0	4"	114,00	4,49	5	75	15	225				2,270	1,53
110,0	4 5/16"	122,00	4,80	5	75	15	225				2,430	1,64
115,0	4 1/2"	127,00	5,00	5	75	15	225				2,530	1,71
127,0	5"	141,00	5,55	5	75	15	225				3,230	2,18