

Dimensions shown may be changed without prior notice

// 650AB

**Fuel-oil delivery 10 bar (150 psi)****Tube:** black conductive NBR.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** grey CR - abrasion, ozone and hydrocarbon resistant.**Application:** general purpose fuel and oil delivery.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↻		↻		↻		↻		↻		↻	↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	35,00	1,38	10	150	30	450				0,640	0,44
32,0	1 1/4"	42,00	1,65	10	150	30	450				0,780	0,53
32,0	1 1/4"	44,00	1,73	10	150	30	450				0,940	0,64
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,910	0,62
38,0	1 1/2"	50,00	1,97	10	150	30	450				1,100	0,74

// 668EL

**Fuel-oil S&D - PVC - Heavy duty****Construction:** blue PVC - abrasion, ozone and hydrocarbon resistant.**Reinforcement:** white shock resistant rigid PVC.**Application:** general purpose fuel and oil suction and delivery.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

↻		↻		↻		↻		↻		↻	↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"			7	100	21	300	150,0	5,91	90	0,540	0,37
32,0	1 1/4"			6	90	18	270	192,0	7,56	90	0,680	0,46
38,0	1 1/2"			6	90	18	270	228,0	8,98	90	0,760	0,52
40,0	1 9/16"			6	90	18	270	240,0	9,45	90	0,800	0,54
51,0	2"			5	75	15	225	306,0	12,05	90	1,150	0,78
60,0	2 3/8"			4	60	12	180	360,0	14,17	90	1,550	1,05
63,0	2 1/2"			4	60	12	180	378,0	14,88	90	1,600	1,08
76,0	3"			4	60	12	180	456,0	17,95	90	2,000	1,35
80,0	3 1/8"			4	60	12	180	480,0	18,90	90	2,100	1,42
102,0	4"			3	45	9	135	612,0	24,09	90	3,100	2,09