

Dimensions shown may be changed without prior notice

// 957LL

**Cable cooling 20 bar (300 psi) - Non conductive****Tube:** white EPDM.**Reinforcement:** high tensile textile cords.**Cover:** white non conductive EPDM, heat resistant - resin coated dust free fibreglass cover.**Application:** non conductive cable cooling in electric furnaces. Specially designed to withstand heat, splashes of molten metal and open flame.**Constant operation:** -40 °C +120 °C (-40 °F +248 °F)
cover resistant up to 540 °C (1000 °F)

↔		↔		↻		↻		↵		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	25,00	0,98	20	300	60	900				0,420	0,29
19,0	3/4"	31,00	1,22	20	300	60	900				0,690	0,47
25,0	1"	37,00	1,46	20	300	60	900				0,850	0,58
32,0	1 1/4"	46,00	1,81	20	300	60	900				1,250	0,85
38,0	1 1/2"	54,00	2,13	20	300	60	900				1,440	0,97
51,0	2"	67,00	2,64	20	300	60	900				1,900	1,28
63,0	2 1/2"	81,00	3,19	20	300	60	900				2,630	1,77
76,0	3"	96,00	3,78	20	300	60	900				3,570	2,40