



Continuous band available in smooth version or with thread stamping throughout

5 different closure types to suit a huge variety of applications



Continuous band clamping system

Consisting of a continuous band, the **NORMAFIX®** **NORMETTA®** system is able to adapt itself to the shape and size of various objects. 5 different types of closure are available to choose from. The system is particularly suitable for carrying out retaining and repair work under difficult and extreme conditions.



Advantages at a glance

- Flexible and versatile
- Can be installed under difficult conditions

Applications

- Irrigation systems
- Railway industry
- Building machines
- Pump and filter
- Retaining applications; sealing pipes during repair work
- Attaching signs and containers
- Binding hoses

Materials

W1	W2	W3	W4	W5
x	x	x	x	

Product and closure types

The continuous band is available in a 30 m roll and as either a smooth version with a range of band widths or a version with thread stamping throughout (with 12 mm band width only). It can also be supplied in different material grades.

Smooth band



To be used with the buckles NB-A W1, NB-D W4 and NB-H W4.

NORMAFIX® NORMETTA SMOOTH BAND					
Width	Thickness	Designation	Length in m	W1 Product No.	W4 Product No.
5	0.35	NORMETTA SMOOTH BAND 30M/5 W1	30	0560 8500 004	
9	0.44	NORMETTA SMOOTH BAND 30M/9 W1	30	0560 8500 001	
	0.5	NORMETTA SMOOTH BAND 30M/9 W4	30		0560 5000 009
13	0.7	NORMETTA SMOOTH BAND 30M/13 W4	30		0560 5000 013
16	0.7	NORMETTA SMOOTH BAND 30M/16 W4	30		0560 5000 016
19	0.7	NORMETTA SMOOTH BAND 30M/19 W4	30		0560 5000 019



Refer to pages 190 and 196.

Stamped band



To be used with the buckles NB-G W3

NORMAFIX® NORMETTA STAMPED BAND					
Width	Thickness	Designation	Length in m	Resistance to traction in N	W3 Product No.
12	0.8	NORMETTA STAMPED BAND 30M/12 W3	30	2600 N	0560 8566 003



Refer to page 196.

Perforated Band



To be used with buckles NB-K W2.

NORMAFIX® NORMETTA PERFORATED BAND						
Width	Thickness	Designation	Length in m	Resistance to traction in N	W2 Product No.	W4 Product No.
8	0.6	NORMETTA PERFORATED BAND 25M/8 W2	25	790 N	0817 7020 001	
	0.6	NORMETTA PERFORATED BAND 25M/8 W4	25	790 N		0817 7022 001
13	0.6	NORMETTA PERFORATED BAND 25M/13 W4	25	850 N		0817 7022 002
14	0.6	NORMETTA PERFORATED BAND 25M/14 W2	25	850 N	0817 7020 002	



Refer to page 196.